

IPLC Interfaces

Data Rate	Functional Characteristics	Electrical Characteristics	Physical Characteristics	Notes
Analogue 2 - Wire	ETSI EN 300448	ETSI EN 300448	ETSI EN 300448	-
Analogue 4 - Wire	ETSI EN 300448	ETSI EN 300448	ETSI EN 300448	-
64kbps	V.35	V.11 & V.28	ISO2593	Option 1
	G.703 co-directional	G.703	DB25	Option 2
	X.21	X.27	DB15	Option 3*
	V.24	V.28	DB25	Option 4*
NX64 (N = 2 to 31)	V.35	V.11 & V.28	ISO2593	Option 1
	X.21	X.27	DB15	Option 2*
2.048kbps	V.35	V.11 & V.28	ISO2593	Option 1
	G.703	G.703 75 Ohm	BNC or IEC1.6/5.6	Option 2
		G.703 120 Ohm		Option 3*
	X.21	X.27	DB15	Option 4*
34Mbps	G.703	G.703 75 Ohm	BNC or IEC1.6/5.6	-
45Mbps	G.703	G.703 75 Ohm	BNC or IEC1.6/5.6	-
155Mbps	G.707	G.957 Optical S.1.1	FC/PC	Option 1
		G.703 75 Ohm	BNC or IEC1.6/5.6	Option 2*

* Non standard interface offered under certain preconditions